

Distribution Class 2 Distributors

Technical Notice

Replacement list for TL-battery types and terminations

Model TL-	Is replaced with model SL-	Degree of conformity	Size	Keyword (SL-model)
		FU = Same function, check with Application Engineering ID = technically identical NS = SL-model is not a standard product TD = TL-model discontinued		
TL-2100	SL-760	FU, TD	AA	Enhanced Start
TL-2134	SL-889	FU, TD	1/10 D	Extended Operating Life
TL-2135	SL-886	FU, TD	1/6 D	Extended Operating Life
TL-2150	SL-750	FU, TD	1/2 AA	Enhanced Start
TL-2155	SL-761	FU, TD	2/3 AA	Enhanced Start
TL-2186	SL-840 => TL-2450	TD, FU	BEL => 1/10 C	Extended Operating Life
TL-2200	SL-2770	FU, TD	C	Enhanced Start
TL-2300	SL-2780	FU, TD	D	Enhanced Start
TL-2450	---		1/10 C	Enhanced Start
TLH-2450	---		1/10 C	Extended Temperature
TL-4902	SL-850	ID	1/2 AA	Extended Operating Life
TL-4903	SL-860	ID	AA	Extended Operating Life
TL-4920	SL-2870	ID	C	Extended Operating Life
TL-4930	SL-2880	ID	D	Extended Operating Life
TL-4934	SL-889	ID	1/10 D	Extended Operating Life
TL-4935	SL-886	ID	1/6 D	Extended Operating Life
TL-4940	---		D	Extended Operating Life w. vent
TLH-4951	SL-550	FU	1/2 AA	Extended Temperature
TL-4955	SL-861	ID	2/3 AA	Extended Operating Life
TL-4986	TL-2450	FU	BEL => 1/10 C	Replacement of different size
TL-5101	SL-350	FU, TD	1/2 AA	Standard Use and Stand-By
TL-5104	SL-360	FU, TD	AA	Standard Use and Stand-By

Model TL-	Is replaced with model SL-	Degree of conformity	Size	Keyword (SL-model)
		FU = Same function, check with Application Engineering ID = technically identical NS = SL-model is not a standard product TD = TL-model discontinued		
TL-5134	SL-889	FU, TD	1/10 D	Extended Operating Life
TL-5135	SL-886	FU, TD	1/6 D	Extended Operating Life
TL-5137	SL-2790	FU, TD	DD	Enhanced Start
TL-5151	SL-350	FU, TD	1/2 AA	Standard Use and Stand-By
TL-5155	SL-361	FU, TD	2/3 AA	Standard Use and Stand-By
TL-5186	SL-840 => TL-2450	TD, FU	BEL => 1/10 C	Extended Operating Life
TL-5215	S2P1/SL-2770	ID	2x C	
TL-5242/W	SL-360/461	NS (on request)	(AA)	Battery Pack
TL-5276/W	SL-750/403	FU	(1/2 AA)	Battery Pack
TL-5293/W	SL-360/486	TD	(2x AA)	Battery Pack
TL-5315/F	---		(2x AA)	Battery Pack
TL-5902	SL-750 {	TD, ID*	1/2 AA	Enhanced Start (*beware of capacity in datasheets -0,1 Ah)
TLL-5902	SL-750	ID*	1/2 AA	Enhanced Start (*beware of capacity in datasheets -0,1 Ah)
TLH-5902	SL-550	ID	1/2 AA	Extended Temperature
TL-5903	SL-760	ID*	AA	Enhanced Start (*beware of capacity in datasheets -0,2 Ah)
TLH-5903	SL-560	ID	AA	Extended Temperature
TL-5920	SL-2770	ID	C	Enhanced Start
TL-5920/B	---		(C)	Battery Pack
TLH-5920	---		C	Extended Temperature
TL-5930	SL-2780	ID	D	Enhanced Start
TL-5930/F	---		(D)	Battery Pack
TLH-5930	---		D	Extended Temperature
TL-5934	---		1/10 D	Enhanced Start (as SL-889)

Model TL-	Is replaced with model SL-	Degree of conformity	Size	Keyword (SL-model)
		FU = Same function, check with Application Engineering ID = technically identical NS = SL-model is not a standard product TD = TL-model discontinued		
TLH-5934	---		1/10 D	Extended Temperature, always w/o disc
TL-5935	---	TD	1/6 D	Enhanced Start
TLH-5935	---		1/6 D	Extended Temperature always w/o disc
TL-5937	SL-2790	ID	DD	Enhanced Start
TL-5955	SL-761	ID	2/3 AA	Enhanced Start
TLH-5955	SL-561	ID	2/3 AA	Extended Temperature
TL-6902	---	PP only	½ AA	Sulfuryl 3,9 V
TL-6903	---	PP only	AA	Sulfuryl 3,9 V
TL-6920	---	PP only	C	Sulfuryl 3,9 V
TL-6930	---	PP only	D	Sulfuryl 3,9 V
TL-6937	---	PP only	DD	Sulfuryl 3,9 V
TL-6955	---	PP only	2/3 AA	Sulfuryl 3,9 V
TL-7902	---	On request	½ AA	TRR Series
TL-7903	---	On request	AA	TRR Series
TL-7920	---	On request	C	TRR Series
TL-7930	---	On request	D	TRR Series
SL-161	SL-761	FU	2/3 AA	Enhanced Start
SL-170	SL-2770	FU	D	Enhanced Start
SL-2361	SL-361	ID	2/3 AA	Old high capacity version, now standard

Model TL-	Is replaced with model SL-	Degree of conformity	Size	Keyword (SL-model)
		FU = Same function, check with Application Engineering ID = technically identical NS = SL-model is not a standard product TD = TL-model discontinued		
SL-340	SL-840 => TL-2450	FU	BEL => 1/10 C	P electrolyte
---	SL-350	TD	1/2 AA	Standard, not available as TL
---	SL-360	TD	AA	Standard, not available as TL
---	SL-361	TD	2/3 AA	Standard, not available as TL
SL-386	SL-886	FU	1/10 D	P electrolyte
SL-389	SL-889	FU	1/10 D	P electrolyte
SL-740	SL-840 => TL-2450	FU	BEL => 1/10 C	iXtra
SL-770	SL-2770	FU	D	Enhanced Start
SL-789	SL-889	FU	1/10 D	Tbd
SL-840	TL-2450	FU	BEL => 1/10 C	Replacement of different size

Termination (TBL)	Termination (TBG)	Size	Designation
/S	/S		Standard
/P	/P	Ø 0,81 x 45 mm	Pins
/T	/T	3,17 x 7 mm	Tabs
/TP	/PTJ	7.5 mm	Polarized Tags double pins (-) 7.5 mm spacing
/PT	/PTPJ	7.5 mm	Polarized Tags double pins (+) 7.5 mm spacing
/PT2	/PR	0,7 x 5,5 mm	Pins Radial